



Specifications Ledvance LED Downlight Biolux HCL Zigbee Gen 2 Aluminium White 20W 2100lm 60D - 927-965 Tunable White | 175mm - Cutout 160mm - IP20 - ZigBee

[View Product](#)

General Information

|                          |                                                     |
|--------------------------|-----------------------------------------------------|
| SKU                      | 253345                                              |
| EAN                      | 4058075724600                                       |
| Brand                    | Ledvance                                            |
| Manufacturer Name        | BIOLUX HCL DOWNLIGHT ZIGBEE GEN 2 DN150 S 20W TW ZB |
| Any Lamp all-in warranty | 5 Years                                             |
| Average Lifetime (h)     | 50000                                               |

Technical Information

|                             |                                      |
|-----------------------------|--------------------------------------|
| Emergency Lighting          | No Emergency Unit                    |
| Tiltable                    | No                                   |
| Technology                  | LED Integrated                       |
| Replaces (Watt)             | 2x18                                 |
| Wattage                     | 20                                   |
| Voltage (V)                 | 220-240                              |
| Dimmable                    | Dimmable with Zigbee                 |
| Colour Code                 | 927 Extra Warm White, 965 Daylight   |
| Colour temperature (Kelvin) | 2700 Extra Warm White, 6500 Daylight |
| Colour Rendering (Ra)       | 90-99                                |
| Colour of Light             | White                                |
| Light colour options        | Tunable White                        |

|                          |                                |
|--------------------------|--------------------------------|
| Beam Angle (degree)      | 60                             |
| Luminous Flux (Lumen)    | 2100                           |
| Luminous Efficacy (lm/W) | 105                            |
| Power factor             | >0.90                          |
| Unified Glare Rating     | < 19 - for offices and schools |
| Optical Cover            | Opal                           |
| Finish of Reflector      | Aluminium                      |
| Product Type Category    | LED Downlight                  |

## Fixture Information

|                        |                             |
|------------------------|-----------------------------|
| Mounting Method        | Recessed                    |
| Cut out (mm)           | 160                         |
| IP-rating              | IP20                        |
| Impact Protection (IK) | IK03 - 0.35 joule           |
| Operating Temperature  | -20 to +40                  |
| Housing                | Aluminium                   |
| Colour of the Fixture  | White                       |
| Fixture Connection     | Terminal, 3-Pole (L, N, PE) |

## Dimensions

|               |     |
|---------------|-----|
| Height (mm)   | 99  |
| Diameter (mm) | 175 |

## Why Any-lamp?

## Sensor Information

 Type of sensor

Order from the **largest lighting specialist** in Europe

No Sensor



**Customised** quotation



Up to **7 years warranty**



**Easy** return process