ANY-LAMP.COM





Specifications Philips LED Downlight Coreline DN145B 6.5W 650lm 90D -830 Warm White | 85mm



View Product

General Information

| SKU | 237297 |
|--------------------------|----------------------------|
| EAN | 8710163339450 |
| Brand | Philips |
| Manufacturer Name | DN145B LED6S/830 PSU II WH |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 50000 |

Technical Information

| Emergency Lighting | No Emergency Unit |
|-----------------------------|-------------------|
| Tiltable | No |
| Technology | LED Integrated |
| Wattage | 6.5 |
| Voltage (V) | 220-240 |
| Dimmable | Not Dimmable |
| Colour Code | 830 Warm White |
| Colour temperature (Kelvin) | 3000 Warm White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Including bulb | Yes |
| | |

| Beam Angle (degree) Luminous Flux (Lumen) 650 Luminous Efficacy (lm/W) 100 Power factor >0.90 Installation Depth (mm) 34 Unified Glare Rating <28 - for hallways and storage rooms Optical Cover PC (Polycarbonate) Finish of Reflector PMMA (Polymethyl methacrylate) Product Type Category LED Downlight | Driver Included | Yes |
|--|--------------------------|---------------------------------------|
| Luminous Efficacy (Im/W)100Power factor>0.90Installation Depth (mm)34Unified Glare Rating< 28 - for hallways and storage rooms | Beam Angle (degree) | 90 |
| Power factor >0.90 Installation Depth (mm) 34 Unified Glare Rating <28 - for hallways and storage rooms Optical Cover PC (Polycarbonate) Finish of Reflector PMMA (Polymethyl methacrylate) | Luminous Flux (Lumen) | 650 |
| Installation Depth (mm) Unified Glare Rating < 28 - for hallways and storage rooms Optical Cover PC (Polycarbonate) Finish of Reflector PMMA (Polymethyl methacrylate) | Luminous Efficacy (lm/W) | 100 |
| Unified Glare Rating < 28 - for hallways and storage rooms Optical Cover PC (Polycarbonate) Finish of Reflector PMMA (Polymethyl methacrylate) | Power factor | >0.90 |
| Optical Cover PC (Polycarbonate) Finish of Reflector PMMA (Polymethyl methacrylate) | Installation Depth (mm) | 34 |
| Finish of Reflector PMMA (Polymethyl methacrylate) | Unified Glare Rating | < 28 - for hallways and storage rooms |
| | Optical Cover | PC (Polycarbonate) |
| Product Type Category LED Downlight | Finish of Reflector | PMMA (Polymethyl methacrylate) |
| | Product Type Category | LED Downlight |

Fixture Information

| EOC8 | 33945099 |
|------------------------|------------------------|
| Mounting Method | Recessed |
| Cut out (mm) | 65 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature | 0 to +35 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | Connection unit 2-pole |
| Series | DN145B |

Dimensions

| Height (mm) | 28 |
|---------------|----|
| Diameter (mm) | 85 |

Sensor Information

Type of sensor

No Sensor

Why Any-lamp?

Order from the **largest lighting specialist** in Europe (**Customised** quotation







Up to 7 years warranty **5** Easy return process

