



Specifications Philips LED Panel TrueLine RC530B 28,5W 4300lm - 940 Cool White | 150x7.5cm - UGR <19 - Dali Dimmable - Best Colour Rendering

# **View Product**

# **General Information**

SKU237453EAN8718699964221BrandPhilipsManufacturer NameRC530B LED43S/940 PSD W8L150 VPC PI5 IPAny Lamp all-in warranty5 YearsAverage Lifetime (h)70000SeriesPanel Led

### **Technical Information**

Technology	LED Integrated
Replaces (Watt)	2x58
Wattage	28.5
Voltage (V)	220-240
Dimmable	Dimmable with Dali
Colour Code	940 Cool White
Colour temperature (Kelvin)	4000 Cool White
Colour Rendering (Ra)	90-99
Colour of Light	White
Light colour options	Single Color
Luminous Flux (Lumen)	4300

Luminous Efficacy (lm/W)	150.9
IP-rating	IP20
Impact Protection (IK)	IK02 - 0.20 joule
Fixture Connection	PI [Push-in connector 3-pole]
Driver Included	Yes
Power factor	>0.90
Product Type Category	LED Panel

# **Fixture Information**

Mounting Method	Recessed
Unified Glare Rating	< 19 - for offices and schools
Optical Cover	PC (Polycarbonate)
Operating Temperature	+10 to +40
Emergency Lighting	No Emergency Unit
Colour of the Fixture	Aluminium
Housing	Steel
Colour of material	Aluminium

# **Dimensions**

LED panel size	150x7.5cm
Length (mm)	1497
Width (mm)	75
Height (mm)	90

Sensor ក្រាស្រែក្រាងទៀតកាthe largest lighting specialist in Europe 🔋 Customised quotation

Type of sensor



**Easy** return process

