



Specifications Philips LED Downlight LuxSpace Square
DN572B VLC-E 20.9W 2600lm 80D - 840 Cool White | 214mm -
Aluminium Reflector - Dali Dimmable

[View Product](#)

General Information

| | |
|--------------------------|----------------------------------|
| SKU | 238760 |
| EAN | 8718699970833 |
| Brand | Philips |
| Manufacturer Name | DN572B LED24S/840 PSD-VLC-E C WH |
| Any Lamp all-in warranty | 5 Years |
| Average Lifetime (h) | 70000 |

Technical Information

| | |
|-----------------------------|-------------------|
| Emergency Lighting | No Emergency Unit |
| Tiltable | No |
| Technology | LED Integrated |
| Voltage (V) | 220-240 |
| Dimmable | Dimmable |
| Colour Code | 840 Cool White |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra) | 80-89 |
| Colour of Light | White |
| Light colour options | Single Color |
| Driver Included | Yes |
| Beam Angle (degree) | 80 |
| Luminous Efficacy (lm/W) | 136 |
| Power factor | >0.90 |

| | |
|-------------------------|--------------------------------|
| Installation Depth (mm) | 96 |
| Unified Glare Rating | < 19 - for offices and schools |
| Optical Cover | PC (Polycarbonate) |
| Finish of Reflector | PC (Polycarbonate) |
| Product Type Category | LED Downlight |

Fixture Information

| | |
|------------------------|-----------------------------------------|
| EOC8 | 97083300 |
| Mounting Method | Recessed |
| Cut out (mm) | 200x200 |
| IP-rating | IP20 |
| Impact Protection (IK) | IK02 - 0.20 joule |
| Operating Temperature | +10 to +25 |
| Housing | Aluminium |
| Colour of the Fixture | White |
| Colour of material | White |
| Fixture Connection | PIP [Push-in connector and pull relief] |
| Series | DN572B |

Dimensions

| | |
|---------------|-----|
| Height (mm) | 119 |
| Diameter (mm) | 214 |

Why Any-lamp?

Sensor Information

 Order from the **largest lighting specialist** in Europe  **Customised** quotation
Type of sensor **No Sensor**

 **Up to 7 years warranty**  **Easy return process**