



Specifications Noxion LED Panel Delta Pro V2.0 Highlum 40W 5480lm - 865 Daylight | 120x30cm - UGR <19 - Philips Xitanium Driver

[View Product](#)

## General Information

|                          |                                                                              |
|--------------------------|------------------------------------------------------------------------------|
| SKU                      | 237861                                                                       |
| EAN                      | 8719157012089                                                                |
| Brand                    | Noxion                                                                       |
| Manufacturer Name        | NEW Noxion LED Panel Delta Pro UGR<19 Highlum V2.0 40W 5480lm 6500K 300x1200 |
| Any Lamp all-in warranty | 6 Years                                                                      |
| Average Lifetime (h)     | 70000                                                                        |
| Series                   | Delta Pro                                                                    |

## Technical Information

|                             |                |
|-----------------------------|----------------|
| Technology                  | LED Integrated |
| Replaces (Watt)             | 2x36           |
| Wattage                     | 40             |
| Voltage (V)                 | 220-240        |
| Dimmable                    | Not Dimmable   |
| Colour Code                 | 865 Daylight   |
| Colour temperature (Kelvin) | 6500 Daylight  |
| Colour Rendering (Ra)       | 80-89          |
| Colour of Light             | White          |
| Light colour options        | Single Color   |
| Luminous Flux (Lumen)       | 5480           |

|                          |                        |
|--------------------------|------------------------|
| Luminous Efficacy (lm/W) | 125                    |
| IP-rating                | IP20                   |
| Impact Protection (IK)   | IK02 - 0.20 joule      |
| Fixture Connection       | PI [Push-in connector] |
| Driver Included          | Yes                    |
| Power factor             | >0.90                  |
| Product Type Category    | LED Panel              |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Recessed                       |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PS (Polystyrene)               |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | PS (Polystyrene)               |
| Colour of material    | White                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 120x30cm |
| Length (mm)    | 1195     |
| Width (mm)     | 295      |
| Height (mm)    | 32       |

## Sensor Information

Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



Up to **7 years warranty**

No Sensor



**Easy** return process