



Specifications Philips LED Panel FlexBlend SP340P  
39W 5200lm - 940 Cool White | 150x20cm - UGR <19 -  
Zigbee Dimmable - Best Colour Rendering

[View Product](#)

## General Information

|                          |                                         |
|--------------------------|-----------------------------------------|
| SKU                      | 238836                                  |
| EAN                      | 8719514103832                           |
| Brand                    | Philips                                 |
| Manufacturer Name        | SP340P 52S/940 SRD PCS SWZU SMT L150 WH |
| Any Lamp all-in warranty | 5 Years                                 |
| Average Lifetime (h)     | 50000                                   |
| Series                   | Panel Led                               |

## Technical Information

|                             |                 |
|-----------------------------|-----------------|
| Technology                  | LED Integrated  |
| Replaces (Watt)             | 2x58            |
| Wattage                     | 39              |
| Voltage (V)                 | 220-240         |
| Dimmable                    | Not Dimmable    |
| Colour Code                 | 940 Cool White  |
| Colour temperature (Kelvin) | 4000 Cool White |
| Colour Rendering (Ra)       | 90-99           |
| Colour of Light             | White           |
| Light colour options        | Single Color    |
| Luminous Flux (Lumen)       | 5200            |

|                          |                   |
|--------------------------|-------------------|
| Luminous Efficacy (lm/W) | 134               |
| IP-rating                | IP20              |
| Impact Protection (IK)   | IK02 - 0.20 joule |
| Fixture Connection       | Terminal, 5-pole  |
| Driver Included          | Yes               |
| Power factor             | >0.90             |
| Product Type Category    | LED Panel         |

## Fixture Information

|                       |                                |
|-----------------------|--------------------------------|
| Mounting Method       | Suspended                      |
| Unified Glare Rating  | < 19 - for offices and schools |
| Optical Cover         | PC (Polycarbonate)             |
| Operating Temperature | -10 to +40                     |
| Emergency Lighting    | No Emergency Unit              |
| Colour of the Fixture | White                          |
| Housing               | Steel                          |
| Colour of material    | White                          |

## Dimensions

|                |          |
|----------------|----------|
| LED panel size | 150x20cm |
| Length (mm)    | 1470     |
| Width (mm)     | 200      |
| Height (mm)    | 73       |

 **Sensor Information** Order from the **largest lighting specialist** in Europe  **Customised** quotation

Type of sensor



**Up to 7 years warranty**

No Sensor



**Easy return process**